



55 cm catheter length 1018 inch dia. spring-wire guide





- One Lumen Catheter: 4 Fr. (1.45 mm OD) x 55 cm, Pressure Injectable, T-Port Connector, Blue FlexTip®, Contamination Guard and Placement Wire
- GlideThru™ Peel-Away Sheath: 4 Fr. x 2-3/4" (7 cm) Radiopaque over 4 Fr.
- Dilator
 Spring-Wire Guide, Nitinol, Marked: .018" (0.46 mm) dia. x 17-3/4" (45 cm)
 (Straight Soft Tip on One End Straight Stiff Tip on Other) with Arrow Advancer
 Injection Needle: Eclipse™1 22 Ga. x 1-5/8" (4 cm)
 Injection Needle: Eclipse™1 25 Ga. x 1* (2.54 cm)
 Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW
 Filter Needle: 18 Ga. TW x 1-1/2" (3.81 cm) with Blunt Fill Tip

- Syringe: 10 mL Luer-Lock
 Syringe: 3 mL Luer-Lock
 Syringe: 3 mL Luer-Lock
 SecondSite™ Adjustable Hub: Catheter Clamp
 SecondSite™ Adjustable Hub: Fastener
 SharpsAway® II Locking Disposal Cup
 SharpsAway® Disposal Cup

- Catheter Trimmer

- Catheter Infilmer
 Towel: 24" x 36" (61 cm x 91 cm)
 Drape: 60" x 76" (152 cm x 193 cm)
 Drape: 36" x 41" (91 cm x 104 cm) with 3" x 5" (8 cm x 13 cm) fenestration
- Safety Scalpel: #11 Patient ID Card
- Sterile Procedure Sign Patient Information Booklet
- Chart Sticker
- PICC Line Insertion Checklist Paper Tape Measure

- Tourniquet
 Gauze Pad: 2" x 2" (5 cm x 5 cm)
 Gauze Pad: 4" x 4" (10 cm x 10 cm)
 Dressing: Tegaderm®2 I.V. Advanced 3-1/4" x 4-1/2" (8.5 cm x 11.5 cm)
 Dressing: GRIP-LOK®3 Catheter Fixation Device
 Surgical Apparel: Cap

- Surgical Apparel: Impervious Gown Dressing: Steri-Strip®2 1/2" x 4" (1.2 cm x 10 cm) Surgical Apparel: Mask
- Surgical Apparel: Mask with Shield
 Transducer Cover: 4-12/16" x 95" (12 cm x 244 cm)
 Valve: MicroCLAVE™4 Neutral Displacement Connector
- HemoHopper® Fluid Recentacle
- ¹A trademark of Becton, Dickinson and Company.

²A registered trademark of 3M Company. ³A registered trademark of TIDI. ⁴A trademark of ICU Medical, Inc.

All components are CE 2797 unless otherwise noted

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. www.teleflex.com/IFU

Not made with natural rubber latex. Fluid path components are non-pyrogenic

Contraindications: The Pressure Injectable PICC is contraindicated wherever there is presence of device related infections or presence of thrombosis in the intended insertion vessel or catheter pathway. Clinical assessment of the patient must be completed to ensure no

Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	Pump Flow Rate†† (mL/hr)	MAX Pressure Injection Flow Rate** (mL/sec)
Distal (18 Ga.)	0.48	436	4075	4

* Priming volumes are approximate and are done without accessories.

† Flow rate values are approximate and are determined using deionized water at 100 cm head

†† Pump flow rates are determined at maximum pump pressure of 10 psig and represent approximate flow capabilities.

** Pressure injection flow rates are determined at the injector pressure setting of 300 psi maximum using media of 11.8 centipoise viscosity, with 152 cm pressure tubing.







Arrow International LLC Subsidiary of Teleflex Incorporated 3015 Carrington Mill Blvd. Morrisville, NC 27560 USA

Teleflex®

LBL069887 R02 (2024-02)



S YYYY-MM-DD






YYYY-MM-DD



(01)XXXXXXXXXXXXXXX (10)Lot Number







Pressure Injectable One-Lumen PICC





ARROW