





Arrowg+ard Blue Plus[®] Two-Lumen CVC

Contents:

- Arrowg+ard Blue Plus®1 Two-Lumen Catheter: 7 Fr. (2.5 mm OD) x 20 cm 1: Spring-Wire Guide, Marked: .032" (0.81 mm) dia. x 23-5/8" (60 cm) (Straight Soft Tip 1: on One End - "J" Tip on Other) with Arrow Advancer with ECG Mark
- 1: Catheter: 18 Ga. x 2-1/2" (6.35 cm) Radiopaque over 20 Ga. RW Introducer Needle
- 1: Introducer Needle: Echogenic 18 Ga. x 2-1/2" (6.35 cm) XTW
- Injection Needle: Eclipse^{™2} 23 Ga. x 1" (2.54 cm) Injection Needle: Eclipse^{™2} 25 Ga. x 1" (2.54 cm) 1:
- 1: 1:
- Pressure Transduction Probe
- Filter Needle: 18 Ga. TW x 1-1/2" (3.81 cm) with Blunt Fill Tip 1:
- 1: Syringe: 5 mL Luer-Lock
- 1: Syringe: 3 mL Luer-Lock
- 1. Arrow® Raulerson Spring-Wire Introduction Syringe: 5 mL
- Tissue Dilator: 8.5 Fr. (2.8 mm) x 10.2 cm SecondSite™ Adjustable Hub: Fastener 1:
- 1:
- SecondSite™ Adjustable Hub: Catheter Clamp 1: SharpsAway® II Locking Disposal Cup
- 1: 1:
- SharpsAway® Disposal Cup 1:
- Towel: 13" x 18" (33 cm x 46 cm)
- 1: Maximal Barrier Drape: 55" x 94-1/2" (140 cm x 240 cm) with 4" (10 cm) fenestration, with adhesive and covered perforation 1.
- Needle Holder
- 1. Safety Scalpel: #11
- Stopcock: 4-way High-Flow 2:
- Sterile Procedure Sign 1.
- 2: Prep Sponge Swab
- 2: Gauze Pad: 2" x 2" (5 cm x 5 cm)

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patier injury or death. www.teleflex.com/IFU Not made with natural rubber latex.

Store below 25°C (77°F). Avoid excessive heat above 40°C (104°F). Fluid path components are non-pyrogenic.

Contraindications: The Arrowg+ard Blue Plus antimicrobial catheter is contraindicated for patients with known hypersensitivity to chlorhexidine, silver sulfadiazine and/or sulfa drugs.

- Gauze Pad: 4" x 4" (10 cm x 10 cm) 6:
- Surgical Apparel: Cap 1: 1.
- Surgical Apparel: Impervious Gown Surgical Apparel: Mask with Shield
- 1: Suture: (0) Silk with Curved Needle 1:
 - Tray: Prep

¹Licensed under US Patent No. 7.329.412. ²A trademark of Becton, Dickinson and Company. All components are CE 2797 unless otherwise noted.

.032 inch dia. spring-wire guide

nt	O Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	
r	Distal (14 Ga.) Proximal (18 Ga.)	0.57 0.40	4731 913	

* Priming volumes are approximate and are done without accessories.

† Flow rate values are approximate and are determined using deionized water at 100 cm head height

