



REF

EU-15703-HPSK

(IPNXXXXXX)



7^{Fr.}

3^{Lumen}

20^{cm catheter length}

.032^{inch dia. spring-wire guide}

Pressure Injectable Three-Lumen CVC

Contents:

- 1: Three-Lumen Catheter: 7 Fr. (2.5 mm OD) x 20 cm, Pressure Injectable
- 1: Spring-Wire Guide, Nitinol, Marked: .032" (0.81 mm) dia. x 23-5/8" (60 cm) (Straight Soft Tip on One End - "J" Tip on Other) with Arrow® GlideWheel™ Wire Advancer with ECG Mark
- 1: Introducer Needle: Echogenic 18 Ga. x 2-1/2" (6.35 cm) XTW
- 1: Injection Needle: Eclipse™¹ 25 Ga. x 1" (2.54 cm)
- 1: Pressure Transduction Probe
- 1: Filter Needle: 18 Ga. TW x 1-1/2" (3.81 cm) with Blunt Fill Tip
- 1: Syringe: 3 mL Luer-Lock
- 1: Syringe: 10 mL Luer-Slip
- 1: Arrow® Raulerson Spring-Wire Introduction Syringe: 5 mL
- 1: Tissue Dilator: 8 Fr. (2.7 mm) x 9 cm
- 3: Dust Cap: Non-Vented
- 1: SecondSite™ Adjustable Hub: Fastener
- 1: SecondSite™ Adjustable Hub: Catheter Clamp
- 1: SharpsAway® II Locking Disposal Cup
- 1: Drape: 47-1/4" x 59" (120 cm x 150 cm) with 4" (10 cm) fenestration, with adhesive
- 1: Safety Scalpel: #11
- 3: Prep Sponge Swab
- 10: Gauze Pad: 4" x 4" (10 cm x 10 cm)
- 1: Dressing: Tegaderm®² I.V. Advanced 3-1/4" x 4-1/2" (8.5 cm x 11.5 cm)
- 1: Dressing: GRIP-LOK®³ Catheter Fixation Device

¹A trademark of Becton, Dickinson and Company.

²A registered trademark of 3M Company.


³A registered trademark of TIDI.

All components are CE 2797 unless otherwise noted.

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. www.teleflex.com/IFU

Not made with natural rubber latex.

Fluid path components are non-pyrogenic.

 Lumen	Priming Volume [‡] (mL)	Gravity Flow Rate [†] (mL/hr)	MAX Pressure Injection Flow Rate ^{**} (mL/sec)
Distal (16 Ga.)	0.47	2656	10
Medial (18 Ga.)	0.40	1245	5
Proximal (18 Ga.)	0.42	1328	5

* Priming volumes are approximate and are done without accessories.

[†] Flow rate values are approximate and are determined using deionized water at 100 cm head height.

^{**} Pressure injection flow rates are determined using media of 11.8 centipoise (cP) viscosity, with 152 cm administration set tubing.


enbehrcsdaneletfifrhudelehuisit

ltnonoplptorusrskslsesvtruk

EU Authorized Representative and Importer:

Teleflex Medical
IDA Business and
Technology Park
Dublin Road, Athlone
Co. Westmeath, Ireland

All components are CE 2797 unless otherwise noted.

 Arrow International LLC
Subsidiary of Teleflex Incorporated
3015 Carrington Mill Blvd.
Morrisville, NC 27560 USA



LOT

LotNumber

 YYYY-MM-DD

 YYYY-MM-DD



(01)XXXXXXXXXXXXXX

(17)YYMMDD

(11)YYMMDD

(10)LotNumber

Product of XXX
Packaged in XXX

Teleflex®
www.teleflex.com

LBL075154 R00 (2024-06)



REF

EU-15703-HPSK

7^{Fr.}

3^{Lumen}

20^{cm catheter length}

.032^{inch dia. spring-wire guide}

Pressure Injectable Three-Lumen CVC

