

REF EU-22702-HPSK (IPNXXXXXX)

7 Fr. 2 Lumen 16 cm catheter length .025 inch dia. spring-wire guide



Pressure Injectable Arrowg+ard Blue® Two-Lumen CVC


Contents:

- 1: Arrowg+ard Blue® Two-Lumen Catheter: 7 Fr. (2.5 mm OD) x 16 cm, Pressure Injectable
- 1: Spring-Wire Guide, Nitinol, Marked: .025" (0.64 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on One End - "J" Tip on Other) with Arrow® GlideWheel™ Wire Advancer
- 1: Introducer Needle: Echogenic 18 Ga. x 2-1/2" (6.35 cm) XTW
- 1: Injection Needle: Eclipse™¹ 25 Ga. x 1" (2.54 cm)
- 1: Pressure Transduction Probe
- 1: Filter Needle: 18 Ga. TW x 1-1/2" (3.81 cm) with Blunt Fill Tip
- 1: Syringe: 3 mL Luer-Lock
- 1: Syringe: 10 mL Luer-Slip
- 1: Arrow® Raulerson Spring-Wire Introduction Syringe: 5 mL
- 1: Tissue Dilator: 8 Fr. (2.7 mm) x 9 cm
- 2: Dust Cap: Non-Vented
- 1: SecondSite™ Adjustable Hub: Fastener
- 1: SecondSite™ Adjustable Hub: Catheter Clamp
- 1: SharpsAway® II Locking Disposal Cup
- 1: Drape: 47-1/4" x 59" (120 cm x 150 cm) with 4" (10 cm) fenestration, with adhesive
- 1: Safety Scalpel: #11
- 3: Prep Sponge Swab
- 10: Gauze Pad: 4" x 4" (10 cm x 10 cm)
- 1: Dressing: Tegaderm®² I.V. Advanced 3-1/4" x 4-1/2" (8.5 cm x 11.5 cm)
- 1: Dressing: GRIP-LOK®³ Catheter Fixation Device

¹A trademark of Becton, Dickinson and Company.
²A registered trademark of 3M Company.

³A registered trademark of TIDI.
All components are CE 2797 unless otherwise noted.

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. www.teleflex.com/IFU
Not made with natural rubber latex.
Store below 25°C (77°F). Avoid excessive heat above 40°C (104°F).
Fluid path components are non-pyrogenic.
Contraindications: The Arrowg+ard Blue antimicrobial catheter is contraindicated for patients with known hypersensitivity to chlorhexidine, silver sulfadiazine and/or sulfa drugs.

 Lumen	Priming Volume [*] (mL)	Gravity Flow Rate† (mL/hr)	MAX Pressure Injection Flow Rate** (mL/sec)
Distal (18 Ga.)	0.33	1079	5
Proximal (14 Ga.)	0.50	4648	10

* Priming volumes are approximate and are done without accessories.
† Flow rate values are approximate and are determined using deionized water at 100 cm head height.
** Pressure injection flow rates are determined using media of 11.8 centipoise (cP) viscosity, with 152 cm administration set tubing.

- en be hr cs da nl et fi fr de el hu is it
- lt no pl pt ro ru sr sk sl es sv tr uk



EU Authorized Representative and Importer:



Teleflex Medical
IDA Business and
Technology Park
Dublin Road, Athlone
Co. Westmeath, Ireland

All components are CE 2797 unless otherwise noted.

