

3 Lumen

16 cm catheter length

Pressure Injectable Arrowg+ard Blue Plus® Three-Lumen

Arrowg+ard Blue Plus®1 Three-Lumen Catheter: 7 Fr. (2.5 mm OD) x 16 cm,

Soft Tip on One End - "J" Tip on Other) with Arrow® GlideWheel™ Wire Advancer

- Pressure Injectable Spring-Wire Guide, Nitinol, Marked: .032" (0.81 mm) dia. x 23-5/8" (60 cm) (Straight
- Introducer Needle: Echogenic 18 Ga. x 2-1/2" (6.35 cm) XTW
- Injection Needle: Eclipse™2 25 Ga. x 1" (2.54 cm)
- Pressure Transduction Probe
- Filter Needle: 18 Ga. TW x 1-1/2" (3.81 cm) with Blunt Fill Tip
- Syringe: 3 mL Luer-Lock
- Syringe: 10 ml Luer-Slip
- 1. Arrow® Raulerson Spring-Wire Introduction Syringe: 5 mL
- 1:
- Tissue Dilator: 8 Fr. (2.7 mm) x 9 cm SecondSite™ Adjustable Hub: Fastener
- SecondSite™ Adjustable Hub: Catheter Clamp
- SharpsAway® II Locking Disposal Cup 1: Towel: 13" x 18" (33 cm x 46 cm)
- Maximal Barrier Drape: 55" x 94-1/2" (140 cm x 240 cm) with 4" (10 cm) fenestration, with adhesive and covered perforation
- 1: Safety Scalpel: #11
- Prep Sponge Swab

- Gauze Pad: 4" x 4" (10 cm x 10 cm) Dressing: Tegaderm $^{@3}$ I.V. Advanced 3-1/4" x 4-1/2" (8.5 cm x 11.5 cm)


Contraindications: The Arrowg+ard Blue Plus antimicrobial catheter is contraindicated for patients with known hypersensitivity to chlorhexidine, silver sulfadiazine and/or sulfa drugs.

- Dressing: GRIP-LOK®4 Catheter Fixation Device 1.
- Surgical Apparel: Cap
- Surgical Apparel: Impervious Gown

- Surgical Apparel: Mask with Shield
- Transducer Cover: 4-12/16" x 95" (12 cm x 244 cm)
- Trav: Prep
- ¹Licensed under US Patent No. 7.329.412.
- ²A trademark of Becton, Dickinson and Company ³A registered trademark of 3M Company.
- ⁴A registered trademark of TIDI.
- All components are CE 2797 unless otherwise noted.

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. www.teleflex.com/IFU Not made with natural rubber latex.	Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	MAX Pressure Injection Flow Rate** (mL/sec)
Store below 25°C (77°F). Avoid excessive heat above 40°C (104°F).				
Fluid path components are non-pyrogenic.	Distal (16 Ga.)	0.38	2490	10
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Medial (18 Ga.)	0.37	1162	5
Contraindications: The Arrowg+ard Blue Plus antimicrobial catheter	Proximal (18 Ga.)	0.39	1328	5

^{*} Priming volumes are approximate and are done without accessories.



































(01)XXXXXXXXXXXXXXX (17)YYMMDD (11)YYMMDD (10)LotNumber

(IPNXXXXXX)







All components are CE 2797 unless otherwise noted.



Product of XXX Packaged in XXX



LBL075229 R00 (2024-06)







[†] Flow rate values are approximate and are determined using deionized water at 100 cm head

height.

** Pressure injection flow rates are determined using media of 11.8 centipoise (cP) viscosity, with
152 cm administration set tubing.