



REF CS-12703-E

(IPNXXXXXX)

16 cm catheter length

1032 inch dia. spring-wire quide

Three-Lumen CVC

- Three-Lumen Catheter: 7 Fr. (2.5 mm OD) x 16 cm Spring-Wire Guide, Marked: .032" (0.81 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on One End "J" Tip on Other)
- Catheter: 18 Ga. x 2-1/2" (6.35 cm) Radiopaque over 20 Ga. RW Introducer Needle
- Introducer Needle: 18 Ga. x 2-1/2" (6.35 cm) XTW
 Pressure Transduction Probe

- Arrow® Raulerson Spring-Wire Introduction Syringe: 5 mL Tissue Dilator: 8.5 Fr. (2.8 mm) x 10.2 cm
- Dust Cap: Non-Vented
- SecondSite™ Adjustable Hub: Fastener SecondSite™ Adjustable Hub: Catheter Clamp
- All components are CE 2797 unless otherwise noted.

Rx	onl	١
----	-----	---

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. www.teleflex.com/IFU

California Prop. 65 ⚠ WARNING: Cancer and Reproductive Harm.

www.P65Warnings.ca.gov
Not made with natural rubber latex.

Fluid path components are non-pyrogenic

Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	
Distal (16 Ga.)	0.4	2947	
Medial (18 Ga.)	0.4	1552	
Proximal (18 Ga.)	0.4	1702	

^{*} Priming volumes are approximate and are done without accessories.



















Teleflex Medical IDA Business and Technology Park
Dublin Road, Athlone
7797 Co. Westmeath, Ireland


All components are CE 2797 unless otherwise noted.

Arrow International LLC Subsidiary of Teleflex Incorporated 3015 Carrington Mill Blvd. Morrisville, NC 27560 USA

Product of xxx Packaged in xxx

Teleflex®

LBL076568 R00 (2025-07)








(01)XXXXXXXXXXXXXXX (17)YYMMDD (11)YYMMDD (10)Lot Number









[†] Flow rate values are approximate and are determined using deionized water at 100 cm head height.