PB-10005-000 Dimensions: Width: 6-3/4" (17,2 cm) Length: 11-5/16" (28,7 cm) T04200100A6 Dimensions: 6 5/8" x 10 1/2"

ARROW

CVC 2 LUMEN

REF ES-14702 (IPNXXXXXX)

7 Fr. 2 Lumen 30 cm catheter length .032 inch dia. spring-wire guide

Two-Lumen CVC

Contents:

1: Two-Lumen Catheter: 7 Fr. (2.5 mm OD) x 30 cm
1: Spring-Wire Guide, Marked: .032" (0.81 mm) dia. x 26-3/4" (68 cm) (Straight Soft Tip on One End - "J" Tip on Other) with Arrow Advancer with ECG Mark
1: Catheter: 18 Ga. x 2-1/2" (6.35 cm) Radiopaque over 20 Ga. RW Introducer Needle
1: Introducer Needle: 18 Ga. x 2-1/2" (6.35 cm) XTW
1: Syringe: 5 mL Luer-Slip
1: Tissue Dilator: 8.5 Fr. (2.8 mm) x 10.2 cm
2: Dust Cap: Non-Vented
1: SecondSite™ Adjustable Hub: Fastener
1: SecondSite™ Adjustable Hub: Catheter Clamp

All components are CE 2797 unless otherwise noted.

Rx only
Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. www.teleflex.com/IFU
Not made with natural rubber latex.
Fluid path components are non-pyrogenic.

MD STERILE EO LATEX

CAS # 7440-48-4

en be bg hr cs da nl et fi fr de el hu is it lv lt no
pl pt ro ru sr sk sl es sv tr uk

Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)
Distal (16 Ga.)	0.57	1917
Proximal (16 Ga.)	0.62	2000

* Priming volumes are approximate and are done without accessories.
† Flow rate values are approximate and are determined using deionized water at 100 cm head height.

EU Authorized Representative and Importer:
EC REP Teleflex Medical IDA Business and Technology Park Dublin Road, Athlone Co. Westmeath, Ireland
CE 2797

All components are CE 2797 unless otherwise noted.

Arrow International LLC
Subsidiary of Teleflex Incorporated
3015 Carrington Mill Blvd.
Morrisville, NC 27560 USA

Product of xxx
Packaged in xxx

LOT Lot Number

YYYY-MM-DD YYYY-MM-DD

(01)XXXXXXXXXXXXXX
(17)YYMMDD
(11)YYMMDD
(10)Lot Number

Teleflex®
www.teleflex.com

LBL076625 R00 (2025-09)

CVC 2 LUMEN
7 Fr. 2 Lumen 30 cm catheter length .032 inch dia. spring-wire guide
REF ES-14702
Two-Lumen CVC
ARROW