## PB-10000-850 8.5 X 10.5



Surgical Apparel: Bouffant Cap

2: Valve: MicroCLAVE<sup>™5</sup> Neutral Displacement Connector

<sup>1</sup>Licensed under US Patent No. 7,329,412 and 11,219,706.

All components are CE 2797 unless otherwise noted.

<sup>2</sup>A trademark of Becton, Dickinson and Company

<sup>3</sup>A registered trademark of C. R. Bard, Inc.

<sup>4</sup>A registered trademark of 3M Company.

5A trademark of ICU Medical, Inc.

Surgical Apparel: Mask

Tape: Steri-Strip®4

1:

1:

1:

- Injection Needle: Eclipse<sup>™2</sup> 25 Ga. x 1" (2.54 cm)
- Safety Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW
- Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW
- Filter Needle: 18 Ga. TW x 1-1/2" (3.81 cm) with Blunt Fill Tip 1.
- Syringe: 10 mL Luer-Lock
- Syringe: 3 mL Luer-Lock
- Dust Cap: Non-Vented 2.
- SecondSite™ Adjustable Hub: Fastener
- SecondSite™ Adjustable Hub: Catheter Clamp
- SharpsAway® Disposal Cup
- SharpsAway® II Locking Disposal Cup
- Catheter Trimmer
- Towel: 24" x 36" (61 cm x 91 cm) 1.
- Maximal Barrier Drape™ with two 13 cm (5") x 15 cm (6") fenestrations
- Towe
- Safety Scalpel: #11 1.
- Patient ID Card 1:
- 1: Sterile Procedure Sign

## +++MR Safe

Not made with natural rubber latex.

Store below 25°C (77°F). Avoid excessive heat above 30°C (86°F)

- Contraindications: The Pressure Injectable Arrowg+ard Blue Advance antimicrobial/antithrombogenic catheter is contraindicated:
- for patients with known hypersensitivity to chlorhexidine
- in the presence of device related infection in the intended insertion vessel or catheter pathway
- in the presence of thrombosis in the intended insertion vessel or catheter pathway

Humen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	Pump Flow Rate†† (mL/hr)	MAX Pressure Injection Flow Rate** (mL/sec)
Pink (18 Ga.)	0.56	350	3050	5
White (18 Ga.)	0.58	360	3100	5

\* Priming volumes are approximate and are done without accessories.

+ Flow rate values are approximate and are determined using deionized water at 100 cm head height.

†† Pump flow rates are determined at maximum pump pressure of 10 psig and represent approximate flow capabilities.

\*\* Pressure injection flow rates are determined at the injector pressure setting of 300 psi maximum using media of 11.8 centipoise viscosity, with 152 cm pressure tubing.

(////CAS # 7440-48-4 \*\*\* MR LBL078853 R00 (2025-04)