











55 cm catheter length

.018 inch dia. spring-wire guide

## Pressure Injectable Arrowg+ard Blue Advance® Two-Lumen PICC pre-loaded with Arrow<sup>®</sup> NaviCurve<sup>™</sup> Stylet



## Contents:

- 1: Two Lumen TaperFree® Catheter‡‡‡ with Arrowg+ard Blue Advance® Antimicrobial/Antithrombogenic Protection<sup>1</sup>: 5.5 Fr. (1.88 mm OD) x 55 cm, Pressure Injectable, Arrow® NaviCurve™ Stylet and T-Port Connector
- GlideThru™ Peel-Away Sheath: 5.5 Fr. x 2-3/4" (7 cm) Radiopaque over 5.5 Fr. Dilator
- Spring-Wire Guide, Nitinol, Marked: .018" (0.46 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on One End - Straight Stiff Tip on Other) with Arrow Advancer
- Injection Needle: SafetyGlide™2 25 Ga. x 5/8" (1.60 cm)
- Safety Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW
- Blunt Fill Needle: 18 Ga. x 1-1/2" (3.81 cm)
- Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW
- Syringe: 5 mL Luer-Lock
- 10 mL Luer-Lock Pre-Filled Saline Syringe
- 5 mL 1% Lidocaine HCl Solution and Alcohol Prep
- 3 mL Applicator 2% CHG and 70% IPA ChloraPrep®3 One-Step Solution
- 3 mL Applicator 2% CHG and 70% IPA ChloraPrep®3 One-Step Solution with Hi-Lite Orange™ Tint
- Dust Cap: Non-Vented
- SharpsAway® II Locking Disposal Cup
- SharpsAway® Disposal Cup
- Catheter Trimmer
- Towel: 24" x 36" (61 cm x 91 cm)
- Maximal Barrier Drape™ with two 13 cm (5") x 15 cm (6") fenestrations
- 1: Safety Scalpel: #11

- Sterile Procedure Sign
- 1: Patient ID Card
- Patient Information Booklet
- Medication Label: 1% Lidocaine
- Paper Tape Measure
- Tourniquet
- Foam Electrodes (3 per pack)
- 10: Gauze Pad: 2" x 2" (5 cm x 5 cm)
- 10: Gauze Pad: 4" x 4" (10 cm x 10 cm)
- Surgical Apparel: Impervious Gown
- Dressing: I.V. Advanced 8.5 cm x 11.5 cm
- Dressing: BIOPATCH®4
- Transducer Cover with Gel and Rubber Bands
- Remote Cover
- SecurePortIV®5 Catheter Securement Adhesive
- Dressing: STATLOCK®6 PICC Plus Catheter Stabilization Device
- Surgical Apparel: Bouffant Cap
- Surgical Apparel: Mask
- Surgical Apparel: Mask with Eve Shield
- Tape: Steri-Strip®7
- 1: T-Piece Cover
- <sup>1</sup>Licensed under US Patent No. 7,329,412 and 11,219,706.
- <sup>2</sup>A trademark of Becton, Dickinson and Company.
- <sup>3</sup>A registered trademark of CareFusion or one of its subsidiaries.
- <sup>4</sup>A registered trademark of Johnson & Johnson Corporation.
- <sup>5</sup>A registered trademark of H.B. Fuller Medical Adhesive Technologies, LLC.
- <sup>6</sup>A registered trademark of C. R. Bard, Inc.

<sup>7</sup>A registered trademark of 3M Company

Not made with natural rubber latex.

Store between 20 - 25°C (68 - 77°F).

Arrow International provides the enclosed medication label(s) for your convenience. Please ensure that these labels are applied to the correct syringe and corresponding medication.

Contraindications: The Pressure Injectable Arrowg+ard Blue Advance antimicrobial/antithrombogenic catheter is contraindicated:

- · for patients with known hypersensitivity to chlorhexidine
- in the presence of device related infection in the intended insertion vessel or catheter pathway
- · in the presence of thrombosis in the intended insertion vessel or catheter pathway

| Lumen          | Priming<br>Volume*<br>(mL) | Gravity<br>Flow<br>Rate†<br>(mL/hr) | Pump<br>Flow Rate††<br>(mL/hr) | MAX Pressure<br>Injection<br>Flow Rate**<br>(mL/sec) |
|----------------|----------------------------|-------------------------------------|--------------------------------|--|
| Pink (18 Ga.)  | 0.56                       | 350                                 | 3050                           | 5  |
| White (18 Ga.) | 0.58                       | 360                                 | 3100                           | 5  |

<sup>\*</sup> Priming volumes are approximate and are done without accessories.





LBL080705 R00 (2025-08)

<sup>†</sup> Flow rate values are approximate and are determined using deionized water at 100 cm head

<sup>††</sup> Pump flow rates are determined at maximum pump pressure of 10 psig and represent

<sup>\*\*</sup> Pressure injection flow rates are determined at the injector pressure setting of 300 psi maximum using media of 11.8 centipoise viscosity, with 152 cm pressure tubing.