PB-10000-850 8.5 X 10.5

This catheter contains CHLORHEXIDINE and SILVER SULFADIAZINE

REF CAN-45703-HUQ1 (IPNXXXXXX)

7 Fr. 3 Lumen 20 cm catheter length .032 inch dia. spring-wire guide

Pressure Injectable Arrowg+ard Blue Plus® Three-Lumen CVC

UDI

Contents:

1: Arrowg+ard Blue Plus®[1] Three-Lumen Catheter: 7 Fr. (2.5 mm OD) x 20 cm, Pressure Injectable
1: Spring-Wire Guide, Nitinol, Marked: .032" (0.81 mm) dia. x 23-5/8" (60 cm) (Straight Soft Tip on One End - "J" Tip on Other) with Arrow® GlideWheel™ Wire Advancer
1: Catheter: 18 Ga. x 2-1/2" (6.35 cm) Radiopaque over 20 Ga. RW Introducer Needle
1: Injection Needle: 25 Ga. x 1-1/2" (3.81 cm)
1: Filter Needle: 18 Ga. TW x 1-1/2" (3.81 cm) with Blunt Fill Tip
1: Introducer Needle: Echogenic 18 Ga. x 2-1/2" (6.35 cm) XTW and 5 mL Arrow® Raulerson Spring-Wire Introduction Syringe
2: Syringe: 5 mL Luer-Lock
1: Tissue Dilator: 8.5 Fr. (2.8 mm) x 10.2 cm
1: SecondSite™ Adjustable Hub: Fastener
1: SecondSite™ Adjustable Hub: Catheter Clamp
1: SharpsAway® II Locking Disposal Cup
1: SharpsAway® Disposal Cup
4: Drape: 30" x 20" (76 cm x 51 cm) with adhesive
1: Towel
1: Safety Scalpel: #11
2: Gauze Pad: 2" x 2" (5 cm x 5 cm)
10: Gauze Pad: 4" x 4" (10 cm x 10 cm)
1: Dressing: I.V. Advanced 8.5 cm x 11.5 cm
1: Transducer Cover: 14 cm x 147 cm
1: Suture: 3-0 Nylon with Straight Needle
3: Valve: MicroCLAVE™[2] Neutral Displacement Connector
1: HemoHopper® Fluid Receptacle

[1]Licensed under US Patent No. 7,329,412.
[2]A trademark of ICU Medical, Inc.

Not made with natural rubber latex.
Store below 25°C (77°F). Avoid excessive heat above 40°C (104°F).
Contraindications: The Arrowg+ard Blue Plus antimicrobial catheter is contraindicated for patients with known hypersensitivity to chlorhexidine, silver sulfadiazine and/or sulfa drugs.

Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	MAX Pressure Injection Flow Rate** (mL/sec)
Distal (16 Ga.)	0.39	2283	10
Medial (18 Ga.)	0.39	913	5
Proximal (18 Ga.)	0.40	996	5

* Priming volumes are approximate and are done without accessories.
† Flow rate values are approximate and are determined using deionized water at 100 cm head height.
** Pressure injection flow rates are determined using media of 11.8 centipoise (cP) viscosity, with 152 cm administration set tubing.

LATEX 25°C (77°F)

LBL081740 R00 (2026-03)